

## EKOKAT PASTE EXTO -THN

### Exterior Paste (Thin)



#### PRODUCT DESCRIPTION

The product is an acrylic copolymer emulsion-based, easy to apply surface smoothing paste that is used for external facades with a thin texture.

#### FEATURES

It acts as a physically resistant filler to fill gaps created as a result of cleaning of previously painted and swollen inner surfaces, and to remove existing defects. Due to the ability to stretch, it prevents the shrinkage cracks from coming out onto the paint. It is resistant to water and moisture. It creates a very solid and even level ground. After drying, any kind of paint can be applied provided that a suitable primer is used. Absorbency is extremely low, and paint consumption is low. It does not hinder the ability of the surfaces to inhale. It saves time and labor.

#### APPLICATION SURFACES

It can be used safely to smooth concrete surfaces, surfaces with mineral plaster or old paint, or rough surfaces on exterior façades, and to fill the shrinkage cracks.

#### APPLICATION

Ekokat Exterior Paste is a ready for use product. Before application, the surface must be cleaned from powder, dirt and grease, and swollen parts should be thoroughly scraped and the surface must be dry. On non - dusting surfaces with a mineral base, low absorbency, or a rough plaster, the exterior application should be performed after EKOKAT PRIMER EXTO – S is applied in one coat. EKOKAT PASTE EXTO - THN Exterior Paste should be applied with a spatula or a flexible steel trowel to make the surface smooth by paying attention to the state of drying between coats. The drying time between coats is 2-4 hours. It is sanded after 24 hours. Any kind of paint can be applied by using suitable primer. The ambient temperature and the temperature of the application surface should be between +5°C and +30°C during the application. The surface with newly applied paste must be protected from breeze and sunlight. It is recommended to clean application tools with water after use. After cleaning the mold grease on gross concrete surfaces, it is recommended to use EKOKAT PRIMER BBA Gross Concrete Primer before application of paste.

#### DILUTION

It is ready for use.

#### DRYING TIME (at 20°C & 65% HR)

Drying Time Before Touch: 1 hours

Final Drying Time: 24 hours (drying time might be longer at higher relative humidity and lower temperature values).

#### CONSUMPTION

It varies between 500-1,000 gr / m<sup>2</sup> in a single coat depending upon the type, absorption, and structure of the application surface.

A controlled sample test should be performed to determine the exact amount of consumption.

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com



# EKOKAT PASTE EXTO -THN

## Exterior Paste (Thin)

### PACKAGING

5 Kg plastic buckets

25 Kg plastic buckets

### STORAGE CONDITIONS

It can be stored for 2 years in its unopened packaging in a cool and dry place, and under protection from direct sunlight and direct sunlight. Close the cover immediately after use so that it does not allow air to enter inside.

### DESCRIPTION OF DANGER

Xi Irritating.

### DANGER PHRASES

R43: May cause sensitisation by skin contact.

### SAFETY PHRASES

Work clothes, protective gloves, goggles and masks suitable for workers health and safety should be used during the application. It should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

S2: Keep out of reach of children.

S 23: Do not breathe vapors


S 24/25: Avoid eye and skin contact.

S 37: Wear suitable gloves.

S 46: If swallowed, seek medical advice immediately and show this container or label.

### RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

EC 512K.001.20  White

EC 512K.002.20  Colored

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com

