

EKOKAT CONCRETE ADD - A

Adherence-enhancing Concrete and Mortar Additive



DESCRIPTION

This products is an acrylic -based adherence enhancing primer.

TECHNICAL SPECIFICATIONS

Appearance	White liquid
Amount of Consumption	200-250 gr/m ²
Drying Time	12-24 hours (23°C)
Appearance of Finished Film	Transparent film
Application Temperature	+5°C to +35°C
Application Tools	Lambskin Roll
<ul style="list-style-type: none">• Depending upon absorbency of concrete surface and ambient temperature.• The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.	

AREAS OF USE

The product is used to increase the splice strength of cement-based materials by reducing the absorbency of surfaces such as plaster, concrete, plaster, screed, wooden; before the performance of applications on old ceramic surfaces; before the performance of applications such as leveling screed, insulation, paint, and etc.; and for prevention of dusting and improvement of productivity.

BENEFITS

It is easy to apply and ready for use. It improves surface adherence. It prevents fast water loss.

INSTRUCTIONS FOR USE

The surface should be clean, dry and sound. Residues (such as plaster, paint, cement residues) that will prevent adhesion on the surface should be removed. Since it is ready for use, EKOKAT CONCRETE ADD – A is mixed well until it becomes homogenous. It is applied in equal thickness to the whole surface with a lambskin roll or brush. These values are valid for a surface and ambient temperature of 20°C. The time is shortened at high temperatures and extended at low temperatures.

PACKAGING

30 kg plastic jerrycans – 220 kg barrels – 1000 kg tanks.

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com



EKOKAT CONCRETE ADD - A

Adherence-enhancing Concrete and Mortar Additive

STORAGE CONDITIONS AND SHELF LIFE

No more than three buckets should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions. Protect from sun and frost.

SAFETY MEASURES

Work clothes, protective gloves, goggles and masks suitable for workers health and safety should be used during the application. It should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

||||| EK 1110.020.30

 White

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com

