


EKOKAT FLEX – S2 ADH

Highly Flexible Adhesive Mortar for Granite and Ceramic



DESCRIPTION

The product is a cement-based, double component, high performance, highly flexible adhesive mortar used for granite and ceramic materials, which contains properties of reduced slippage as well as extended rest time under exposed conditions, and also contains mineral aggregates of a special particle size, and special chemical additives enhancing product performance.

It conforms TS EN 12004, C2TE S2 standards.

C: Cement-based, 2: High performance, T: Reduced slippage, E: Extended Rest Time under Exposed Conditions, S2: Highly flexible.

TECHNICAL SPECIFICATIONS

Appearance	1st Component: Grey powder 2nd Component: White liquid
Mixing Ratio	25 kg powder / 7 kg liquid
Amount of Consumption	4-5 kg/m ²
Application Temperature	+5°C to +30°C
Slippage	≤ 0.5 mm
Vessel Life	4 hours
Initial Splice Strength	≥ 1 N/mm ²
Splice strength after immersed into water	≥ 1 N/mm ²
Splice strength after thermally aged	≥ 1 N/mm ²
Elasticity	≥ 5 mm S2
Temperature Resistance	- 40°C to + 80°C
Fire Reaction	A2 s 1 d0
Time before walk-on	3 hours
Time before availability for traffic	24 hours
* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.	
* If the temperature of the application surface is above +25 ° C, then the surface should be moistened.	

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com



EKOKAT FLEX – S2 ADH

Highly Flexible Adhesive Mortar for Granite and Ceramic

AREAS OF USE

The product is used for ceramic-over-ceramic applications performed at thermal pools where sudden thermal changes occur, at hot springs, at wet areas such as turkish baths, for terrace and garden arrangements, for ceramic, marble, granite, and natural stone coatings of floors and walls, and at places which experience heavy pedestrian and load traffic.

BENEFITS

It is easy to prepare and apply. It sets fast. It has high adhesion strength. It is resistant to freeze-thaw cycling.

INSTRUCTIONS FOR USE

Care must be taken to ensure that the application surface is sound, dry, dust-free, and clean. Residues that will prevent adhesion on the surface should be cleaned. 25 kg of EKOKAT FLEX - S2 ADH is slowly poured into 7 kilograms of liquid component, and mixed with the help of a low revolving mixer or a trowel until a homogeneous consistency is achieved. The mortar should be allowed to rest for 5 minutes and then mixed for one minute. The mortar should be notched with a notched trowel suitable for dimensions of the material used. The affixing process should be performed within 20 to 25 minutes. The mortar should not be used if its usage time has expired and it has been scabbed. Do not apply above 35 ° C or below + 5 ° C.

PACKAGING

25 kg PE reinforced craft bags.

64 shrink bags on one palette (110x110 cm).

7 kg plastic jerrycans.

STORAGE CONDITIONS AND SHELF LIFE


No more than two palettes should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions.


SAFETY MEASURES

Work clothes, protective gloves, goggles, and masks suitable for workers health and safety should be used during the application. It should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

■ EK 1007.010.25  Grey

■ EK 1007.020.25  White

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com

