

EKOKAT PRIMER INTO - GPS

Transparent Plaster Primer with Silicon for Inner Walls

DESCRIPTION

The product is an acrylic emulsion-based, transparent primer with silicon that is used for pre-paint applications of plaster surfaces.

PROPERTIES

It is ready for use. It ensures good adhesion of plaster surfaces to the surface. It reduces sudden water loss by reducing the absorbency of plaster surfaces. It reduces the amount of consumption of the paint to be applied. It prevents the early drying and cracking of the paint under hot weather conditions. It reinforces the surface thanks to its high ability of penetration into the surface with its unfilled structure.

TECHNICAL SPECIFICATIONS

Structure	Acrylic emulsion-based
Color	Transparent
Thinner	Water
Amount of Consumption	0,100 liters/m depending upon surface roughness and absorbency (single coat)
Drying Time	6 hours for paint applications
Application Temperature	+5 °C to +35 °C

* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.

AREAS OF USE

It is used as an emulsion-based paint primer on porous surfaces with high absorbency such as satin, plaster panel, and paste.

BENEFITS

It is easy to prepare and apply. It is ready for use. It provides high adherence to concrete and plaster-applied surfaces. It is resistant to water and frost. It is not affected from temperature differences.

INSTRUCTIONS FOR USE

Dust, swollen coats, dirt, oil, etc. present on application surfaces must be cleaned from the surface. Surfaces with old paints and synthetic surfaces should be cleaned thoroughly. Surfaces should be repaired using EKOKAT PASTE INTO – TCK, if necessary. EKOKAT PRIMER INTO – GPS should be mixed thoroughly before application. EKOKAT PRIMER INTO - GPS should be diluted with water at the ratio of 15 to 20% by volume and mixed well until it becomes homogenous. It should be applied as a single coat by means of a brush, a roll, or a spraying system. A rest time of at least 6 hours should be allowed to lapse before application of paint. The ambient temperature and the temperature of the application surface should be at least +5°C during the application as well as for at least 24 hours thereafter. Application tools should be washed with water immediately after use.

Date: 02.03.2017 Revision: 00

EKOKAT PRIMER INTO - GPS

Transparent Plaster Primer with Silicon for Inner Walls

APPLICATION TOOLS

Roll, brush

PACKAGING

20 kg plastic buckets

STORAGE CONDITIONS AND SHELF LIFE

No more than three buckets should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions.

SAFETY MEASURES

Work clothes, protective gloves, goggles, and masks suitable for workers health and safety should be used during the application. It should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

EC 412K.001.20

 White

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com

